



## Specification of G3H Patient Monitor



**Standard configuration:** ECG, HR, PR, SpO<sub>2</sub>, OxyCRG diagram, ST analysis, Arrhythmia analysis, RESP\*2 (RA-LL impedance and nasal cavity), NIBP (with venous punch), TEMP\*2(surface and rectal type), Drug dose calculation and lead-acid battery.

**Optional configuration:**

- Wireless networking function to patient monitor;
- Inside placed thermal-sensitive built-in printer;
- IBP function (Include 1 pressure sensor and 1 adaptable cable);
- Wall Mount for patient monitor ;
- Trolley for patient monitor;
- 12 volts Power supply for ambulance

### Physical Character

1. Displayer: 8.4" color TFT LCD screen with maximum 8-waveform display.
2. Battery: Rechargeable high-energy built-in battery
3. Advanced streamline outline design, portable, compact, lightweight
4. Operating menu with multi-language interface selection: English, Spanish, Portuguese, Chinese, Arabic, Russian, Italian, etc.
5. Easy operation with user friendly menu structure design and rotary dial
6. Against & eliminate ESU interference & defibrillation, no need to disconnect the monitor from the patient in process of defibrillating.
7. Three-application mode: monitoring, diagnosis, operating.
8. WAN communication function to network with central monitoring system and make long-distance monitoring, diagnosis, maintenance and software upgrade possible
9. Optional built-in wireless networking function
10. 72 hours data storage.
11. Intelligent audio and visual comprehensive alarm
12. In-hospital applications include emergency room's pre and post operative care, ICU, Operation room/theater, ambulatory surgery, intermediate care/step down units, labor and delivery, and hospital-based special procedure areas.
13. Suitable for use in physicians' offices, clinics, outpatient surgical centers, extended care facilities and other patient care areas, which of require affordable monitoring
14. Suitable for adult, pediatrics, neonates



## Specification of G3H Patient Monitor

| Technical Parameter  |             |                |
|--|-------------|----------------|
| <b>Temperature (surface and rectal)</b>                          |             |                |
| Measurement range: 25.0 – 45.0 °C                                |             |                |
| Accuracy: ± 0.1 °C   |             |                |
| Resolution: 0.1 °C   |             |                |
| response time: ≤ 3 min.  |             |                |
| <b>ECG</b>   |             |                |
| Input: 5 wires ECG cable   |             |                |
| Lead section: I , II ,III/ aVR, aVL, aVF/ V                      |             |                |
| Gain (mm/mV) : 1/4, 1/2, 1, 2, 4                                 |             |                |
| Frequency response: Diagnosis 0.05 - 100Hz                       |             |                |
|  | Monitor     | 0.5 - 40 Hz    |
|  | Surgery     | 1.0 - 25 Hz    |
| Sweep speed(mm/sec): 12.5, 25, 50                                |             |                |
| Heart rate range: 30-254 BPM                                     |             |                |
| Heart rate accuracy: ± 1 %                                       |             |                |
| ST segment deviation analysis: -0.8-+0.8mV                       |             |                |
| ST accuracy: ±0.02mv   |             |                |
| <b>Respiration Rate</b> (RA-LL impedance and nasal cavity)       |             |                |
| Measurement range: 0 - 120 BPM ( adult )                         |             |                |
| Accuracy: ± 1 BPM or 5 %   |             |                |
| Resolution: 1 BPM  |             |                |
| <b>Environment</b>   |             |                |
|  | Operation   | Storage        |
| Temperature  | 0.5 - 40 °C | -20 - 50 °C    |
| Relative humidity  | ≤ 80%       |                |
| <b>Pulse Rate</b>  |             |                |
| SPO2 measurement range: 0 - 100 %                                |             |                |
| Resolution: 1 %  |             |                |
| Pulse measurement range: 30- 254BPM                              |             |                |
| Accuracy: ± 2 %  |             |                |
| Resolution: 1 BPM  |             |                |
| <b>NIBP (Non-invasive blood pressure)</b>                        |             |                |
| Measurement type : adult, pediatric, neonatal                    |             |                |
| Measurement range: Systolic 4.0 - 37.0 kPa                       |             |                |
|  | Diastolic   | 1.3 - 33.0 kPa |
|  | Mean        | 2.6 - 35.0 kPa |
| Accuracy : ± 0.4 kPa or 5 %                                      |             |                |
| Resolution: 0.1 kPa  |             |                |
| Protection: over pressure  |             |                |
| <b>IBP(Invasive blood pressure) (with venous punch) (Option)</b> |             |                |
| Measurement range: -1.3~40kPa (-10~300mmHg)                      |             |                |
| Channel: 2 channel   |             |                |
| Transducer sensitivity: 5MV/V/mmHg                               |             |                |
| Unit display: KPa or mmHg selectable                             |             |                |
| <b>Power requirements</b>  |             |                |
| Input: 98~260 V AC, 50/60Hz                                      |             |                |
| Consumption: ≤ 80VA  |             |                |
| <b>Safety standard:</b> IEC 60601-1                              |             |                |
| <b>Quality System:</b> ISO13485: 2003                            |             |                |

### Accessories for Standard configuration:

- 1 set of ECG cable
- 10 pcs of ECG electrode
- 1 set of NIBP extend cable
- 1 set of NIBP adult or pediatric or neonate cuff
- 1 set of RESP nasal cavity pipe
- 1 set of TEMP surface probe
- 1 set of TEMP cavity probe
- 1 set of integrated adult or pediatric or neonate SpO2 sensor
- 1 set of power supply cable